

防电磁型电缆接头

PG系列金属电缆接头

电缆接头 (填料函)

Cable gland

电缆接头 (填料函)

Cable gland



材质 Material	黄铜镀镍 (订货时请指明) Brass nickel plated (When ordering, please specify)		
夹紧件 Claw	尼龙塑料(PA) Nickel plastic(PA)		
密封件 Seals	丁腈橡胶(NBR) NBR	防护等级 Degree of protection	IP68-10巴压力 (旋紧部分) IP68-10 bar (Screwing part)
工作温度 COT	-40°C ~100°C短时120°C -40°C ~100°C, Short time 120°C		



材质 Material	黄铜镀镍 (订货时请指明) Brass nickel plated (When ordering, please specify)		
夹紧件 Claw	尼龙塑料(PA) Nickel plastic(PA)		
密封件 Seals	丁腈橡胶(NBR) NBR	防护等级 Degree of protection	IP68-10巴压力 (旋紧部分) IP68-10 bar (Screwing part)
工作温度 COT	-40°C ~100°C短时120°C -40°C ~100°C, Short time 120°C		



特殊平紧爪与平紧圈之设计, 夹紧电缆范围大, 抗拉力强, 可防水, 防尘抗盐抗盐、耐弱酸、酒精、油、油脂及一般溶剂。

Special design of clamping claw and clamping ring, wide clamping range, high stretching resistance, water proof, dustproof, salt resistant, resistant for weak acid, alcohol, oil, grease and general solvent

特殊平紧爪与平紧圈之设计, 夹紧电缆范围大, 抗拉力强, 可防水, 防尘抗盐抗盐、耐弱酸、酒精、油、油脂及一般溶剂。

Special design of clamping claw and clamping ring, wide clamping range, high stretching resistance, water proof, dustproof, salt resistant, resistant for weak acid, alcohol, oil, grease and general solvent



单位:mm

螺牙规格公制AG Specification of thread (metric)	螺牙规格PG Specification of thread	螺牙规格NPT Specification of thread	螺牙规格G Specification of thread	适用电缆 Cable Range	螺纹长度GL Thread length	接合长度H Joint length	扳手径 Wrench diameter
M12 x 1.5	PG7	NPT1/4	G1/4	6.5-3	7mm	19mm	14mm
M14 x 1.5				8-4	7mm	19mm	18mm
M16 x 1.5	PG9	NPT3/8	G3/8	8-4	8mm	20mm	18mm
M18 x 1.5	PG11			10-5	8mm	21mm	20mm
M20 x 1.5	PG13.5	NPT1/2	G1/2	12-6	8mm	22mm	22mm
M22 x 1.5	PG16			10-14	8mm	23mm	24mm
M24 x 1.5				10-14	9mm	25mm	24/27mm
M25 x 1.5	PG19			10-14	9mm	25mm	24/27mm
M25 x 1.5				18-13	9mm	27mm	30/27mm
M27 x 1.5(2)				18-13	9mm	27mm	30mm
M28 x 1.5(2)	PG21	NPT3/4	G3/4	18-13	9mm	27mm	30mm
M30 x 1.5(2)				18-13	9mm	29mm	30/32mm
M32 x 1.5(2)	PG25			22-15	10mm	29mm	35mm
M33 x 1.5(2)				22-15	10mm	29mm	35mm
M36 x 1.5(2)				25-18	10mm	31mm	40mm
M37 x 1.5(2)	PG29	NPT1	G1	25-18	10mm	31mm	40mm
M40 x 1.5(2)				25-18	11mm	31mm	40/45mm
M40 x 1.5(2)				30-22	11mm	35mm	45mm
M42 x 1.5(2)				30-22	11mm	35mm	45mm
M47 x 1.5(2)	PG36	NPT1 1/4	G1 1/4	33-22	11mm	37mm	50mm
M48 x 1.5(2)				33-25	11mm	37mm	50mm
M50 x 1.5(2)				38-25	12mm	37mm	57/55mm
M54 x 1.5(2)	PG42	NPT1 1/2	G1 1/2	38-32	12mm	38mm	57mm
M56 x 1.5(2)				38-32	12mm	38mm	57/59mm
M60 x 1.5(2)	PG48	NPT2	G2	44-37	13mm	38mm	65mm
M63 x 1.5(2)				44-37	13mm	38mm	65mm
M64 x 1.5(2)				44-37	13mm	38mm	65/68mm
M72 x 2	PG63	NPT2 1/2	G2 1/2	52-42	15mm	42mm	77mm
M75 x 2				52-42	15mm	42mm	77mm
M80 x 2				62-55	15mm	45mm	90mm
M88 x 2		NPT3	G3	70-65	15mm	45mm	94mm
M100 x 2				84-78	15mm	45mm	110mm



单位:mm

螺牙规格AG Specification of thread	适用电缆 Cable Range	螺牙外径 Outer diameter of thread	机板口径 Mounting hole diameter	螺纹长度GL Thread length	螺纹长度加长型GL Thread length (lengthened type)	接合长度H Joint length	扳手径 Wrench diameter
PG7	6.5-3	12.5mm	12.5-12.7mm	7mm	10mm	19mm	14mm
PG9	8-4	15.2mm	15.2-15.4mm	8mm	10mm	20mm	17mm
PG11	10-5	18.6mm	18.6-18.8mm	8mm	10mm	21mm	20mm
PG13.5	12-6	20.4mm	20.4-20.6mm	8mm	15mm	22mm	22mm
PG16	10-14	22.5mm	22.5-22.7mm	9mm	15mm	23mm	24mm
PG19	10-14	25mm	25-25.2mm	9mm	15mm	25mm	24/27mm
PG21	18-13	28.3mm	28.3-28.5mm	9mm	15mm	27mm	30mm
PG25	22-15	32mm	32-32.2mm	10mm	15mm	29mm	35mm
PG29	25-18	37mm	37-37.2mm	11mm	15mm	31mm	40mm
PG36	33-25	47mm	47-47.2mm	12mm	15mm	37mm	50mm
PG42	38-32	54mm	54-54.2mm	13mm	15mm	38mm	57mm
PG48	44-37	59.3mm	59.3-59.5mm	14mm	15mm	38mm	65mm
PG63	52-42	72mm	72-72.2mm	15mm	20mm	42mm	77mm